

## **TORCH FUME EXTRACTION**



Designed to significantly reduce exposure to harmful welding fumes directly at the source. Specialized extraction system that efficiently draws in fumes directly from the torch head, minimizing exposure to harmful pollutants, providing a safer and healthier welding environment.



#### **Key Features:**

- Easy Connect with Fume Extraction MIG Torches
- 200±10m³/h air volume
- 1.2 kw motor power
- Digital Display
- Air Volume Adjustment
- Replaceable Cartridge
- 360° Swivel Casters






NACODE!	
MODEL	EX-1
Part Number	681010
FILTER	
Filter Material	PET
Fiterable Fume Size	0.3 µm
Filterability	99.90%
Filter Cartridge	Ø 230 x 176 mm
Filter Area	6 m <sup>2</sup>
Control System	Delixi
TECHNICAL DATA	
Aspirating Volume	200+10m³/h
Motor Power	1.2 kW
Power Supply	240V/50Hz
<b>Blower Loading Pressure</b>	26000 Pa
<b>Dust Outlet Diameter</b>	50 mm
Air Compression	0.5~0.6 Mpa
Noise dB	≤70±5 dB (A)
Fume Removal Method	Manual
Fume Cartridge Volume	5L
Dimensions	600 x 285 x 527 mm
Weight	24 kg

### **FUME EXTRACTION MIG TORCHES**





#### **Key Features:**

- Absorb Fume from Nozzle
- LED Light
- Gun Handle Option
- Euro Connector
- Length: 4m









### 24 STYLE

P/N: 92.FE.24.4

- Air Cooled
- 60% @ 250A CO2 60% @ 220A Mixed Gas
- Wire Size: 0.8 1.2mm

# **36 STYLE** P/N: 92.FE.36.4

P/N. 92.FE.30.

- Air Cooled
- 60% @ 340A CO2 60% @ 300A Mixed Gas
- Wire Size: 0.8 1.6mm

## **501 STYLE** P/N: 92.FE.501.4

- \\/atau Oaala

- Water Cooled
- 100% @ 500A CO2 100% @ 450A Mixed Gas
- Wire Size: 1.0 1.6mm