

K60 AIR COMPRESSOR – 415V THREE PHASE

PISTON DISPLACEMENT (to AS4637)	1,698 L/MIN ~ 60 CFM
FREE AIR DELIVERY (to AS4637)	1,353 L/MIN ~ 47.8 CFM
MAXIMUM CUT OUT PRESSURE	1100 KPA ~ 160 PSI
COMPRESSOR PUMP	FOUR CYLINDER, TWO STAGE, ITALIAN MADE
MOTOR	11 KW ~ 15 HP 415V THREE PHASE 50HZ COMPLETE WITH STAR DELTA STARTER NOTE: NOT SUPPLIED WITH LEAD & PLUG
REQUIRED CIRCUIT BREAKER	40 AMP **
RECEIVER	267 LITRE (STATIC), TO AS1210, AUSTRALIAN MADE
DIMENSIONS	1770mm L X 680mm W X 1260mm H
WEIGHT	340 KG*
AIR OUTLET	3/4" BSP

* APPROX ONLY
** INDICATIVE ONLY, PLEASE CHECK WITH YOUR ELECTRICIAN



FEATURES

- AUSTRALIAN DESIGNED AND BUILT
- INDUSTRIAL GRADE HAMMERTONE ENAMEL FINISH
- CAST IRON CYLINDER PUMP
- ELECTRIC MOTOR OVERLOAD
- WARRANTY: 3 YEARS ON PUMP, 1 YEAR ON ALL OTHER COMPONENTS